

KENWOOD

Listen to the Future



ProTalk® TK-2302V16P/3302U16P

Compact VHF/UHF FM Portable Radios

Kenwood's compact and rugged TK-2302V16P/TK-3302U16P transceivers represent ergonomic and quality excellence. Based upon a proven design with enhanced features, it has the power and performance to satisfy the toughest job requirements. You will immediately appreciate how easy it is to use and enjoy features such as scan, built-in VOX, and long battery life. It has reliable performance in all conditions, thanks to MIL-STD 810 & IP54/55 weatherproofing. Indoors or out, rain or shine, the smart new high-powered ProTalk® on-site radios are star performers!

COMPACT DESIGN

The ProTalk®'s rounded ergonomic contours naturally fit the hand for a superbly comfortable hold, while the non-slip elastomer channel knob with improved torque characteristics ensures positive select operation.

TOUGH & WATER RESISTANT

Built tough to take rough treatment in stride, the TK-2302V16P/TK-3302U16P has passed the demanding IP54/55 dust and water intrusion tests, both with or without the KMC-45 optional speaker microphone. They meet or exceed 11 stringent MIL-STD 810 C/D/E/F environmental standards including driven rain. So, whatever the weather, the ProTalk® radios are ready for action.

FUNCTION KEYS

The two side PF1 and PF2 keys make functions easily available on the TK-2302V16P/TK-3302U16P, with PF1 key for activating the Lock function and PF2 key for Scan w/temp delete function permitting a custom usage for specific users.

LOCK

Lock all user controls (except PTT and volume) to prevent accidental channel changes.

SCAN

Scanning is a simple way to monitor multiple channels and the TK-2302V16P/TK-3302U16P (16-channel capacity) offers scan modes.

VOICE ANNUNCIATION

When you select different channels, these ProTalk® radios can be set to provide voice annunciation channel numbers.

WIRELESS CLONING

This wireless feature simplifies the setup of several radios to function identically and eliminates repetitive setup actions of individual radios. (Dealer function only)

ACCESSORIES INCLUDED

- 12-Hour Li-Ion Battery (5-5-90)
- 3-Hour Fast Charger
- Spring Action Belt Clip
- Removable Antenna

OTHER FEATURES

- Weighs only 9.9 oz
- VOX Hands-Free Operation
- Time-Out-Timer
- Low Battery Warning
- 2-Year Warranty



Options

<ul style="list-style-type: none"> ■ KNB-45L Li-Ion Battery Pack (2000 mAh) ■ KSC-35K Fast Charger (3-Hour) ■ KRA-16 VHF Stubby Antenna ■ KRA-17 UHF Stubby Antenna ■ KRA-22 VHF Low Profile Helical Antenna ■ KRA-23 UHF Low Profile Helical Antenna ■ KRA-26 VHF Helical Antenna 	<ul style="list-style-type: none"> ■ KRA-27 UHF Whip Antenna ■ KMC-45 Speaker Microphone ■ KMC-21 Compact Speaker Microphone ■ KEP-2 Earphone Kit (2.5mm plug) ■ KHS-7 Single-Muff Headset ■ KHS-7A Single-Muff Headset with In-Line PTT 	<ul style="list-style-type: none"> ■ KHS-8BL/BE 2-wire Palm Mic with Earphone (Black/Belge) ■ KHS-9BL/BE 3-wire Lapel Mic with Earphone (Black/Belge) ■ KHS-22 Behind-the-head Headset with PTT ■ KHS-23 2-wire Palm Mic ■ KHS-25 D-Ring Ear Hanger with PTT & Boom Mic ■ KHS-26 Earbud In-line PTT Headset 	<ul style="list-style-type: none"> ■ KHS-27 D-Ring In-line PTT Headset ■ KMB-25 Six Unit Charger Adapter ■ KMB-28 Six Unit Charger Adapter for six KSC-35K chargers ■ KBH-10 Belt Clip ■ KWR-1 Water Resistance Bag ■ KLH-126 Nylon Case
--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

All accessories and options may not be available in all markets.
Contact an authorized Kenwood dealer for details and complete list of all accessories and options.

Specifications

Model	TK-2302V16P	TK-3302U16P
GENERAL		
Frequency Range	136-174 MHz	450-490 MHz
Number of Channels	16	
Channel Spacing	Wide/Narrow 25 kHz/12.5 kHz	
Operating Voltage	7.5V DC±20%	
Battery Life (5-5-90 during hi-power battery saver: OFF/ON)	with KNB-45L (2000mAh) Approx. 12 hours / 18 hours	
Operating Temperature Range	-22°F ~ +140°F (-30°C ~ +60°C)	
Frequency Stability	±2.5 ppm (-30°C ~ +60°C)	
Antenna Impedance	50 Ω	
Dimensions (W x H x D), Projections not included	with KNB-45L 2.13" x 4.8" x 1.33" (54 x 122 x 33.8 mm)	
Weight (Net)	Radio Only 5.6oz (160g) with KNB-45L 9.9oz (280g)	
FCC ID	Type 1 ALH413500 ALH413600	

Kenwood follows a policy of continuous advancement in development.
For this reason specifications may be changed without notice.

ProTalk® is a registered trademark of Kenwood Corporation.

Model	TK-2302V16P	TK-3302U16P
RECEIVER (Measurements made per TIA/EIA-603)		
Sensitivity (12dB SINAD)	Wide 0.25 μV Narrow 0.28 μV	
Selectivity	Wide 70 dB Narrow 60 dB	
Intermodulation Distortion	Wide 65 dB Narrow 60 dB	
Spurious Response	65 dB	60 dB
Audio Output (4 Ω Impedance)	500mW with less than 10% distortion	
TRANSMITTER (Measurements made per TIA/EIA-603)		
RF Power Output	High 5 W Low 1 W	4 W 1 W
Spurious Response	65 dB	
Type of Emission	Wide 16K0F3E Narrow 11K0F3E	
FM Noise (EIA)	Wide 45 dB Narrow 40 dB	
Audio Distortion	Less than 5%	
Microphone Impedance	2 kΩ	

Applicable MIL-STD & IP

Standard	MIL 810C Methods/Procedures	MIL 810D Methods/Procedures	MIL 810E Methods/Procedures	MIL 810F Methods/Procedures
Low Pressure	500.1/Procedure I	500.2/Procedure I, II	500.3/Procedure I, II	500.4/Procedure I, II
High Temperature	501.1/Procedure I, II	501.2/Procedure I, II	501.3/Procedure I, II	501.4/Procedure I, II
Low Temperature	502.1/Procedure I	502.2/Procedure I, II	502.3/Procedure I, II	502.4/Procedure I, II
Temperature Shock	503.1/Procedure I	503.2/Procedure I	503.3/Procedure I	503.4/Procedure I, II
Solar Radiation	505.1/Procedure I	505.2/Procedure I	505.3/Procedure I	505.4/Procedure I
Rain	506.1/Procedure I, II	506.2/Procedure I, II	506.3/Procedure I, II	506.4/Procedure I, III
Humidity	507.1/Procedure I, II	507.2/Procedure II, III	507.3/Procedure II, III	507.4
Salt Fog	509.1/Procedure I	509.2/Procedure I	509.3/Procedure I	509.4
Dust	510.1/Procedure I	510.2/Procedure I	510.3/Procedure I	510.4/Procedure I, III
Vibration	514.2/Procedure VIII, X	514.3/Procedure I	514.4/Procedure I	514.5/Procedure I
Shock	516.2/Procedure I, II, V	516.3/Procedure I, IV	516.4/Procedure I, IV	516.5/Procedure I, IV
International Protection Standard				
Dust & Water Protection	IP54/55			

*To meet IP54/55, the 2-pin connector cover has to be connected on the radio; the locking bracket has to be attached to the KMC-45 external speaker microphone.



1435 Holmes Rd.
Elgin, IL 60123
847 695-6938

